

Schema Easypanel ModoFila

Project name = main

Shema:

```
{
  "services": [
    {
      "type": "app",
      "data": {
        "projectName": "main",
        "serviceName": "n8n_editor",
        "source": {
          "type": "image",
          "image": "n8nio/n8n:latest"
        },
        "env":
"DB_TYPE=postgresdb\r\nDB_POSTGRESDB_PORT=5432\r\nDB_POSTGRESDB_HOST=main_n8n_pos
gres\r\nDB_POSTGRESDB_DATABASE=n8n\r\nDB_POSTGRESDB_USER=postgres\r\nDB_POSTGRES
DB_PASSWORD=e8a8bhc40zj2os5wizlm\r\n# criar chave
https://acte.ltd/utils/randomkeygen=\r\nN8N_ENCRYPTION_KEY=e8a8bhc40zj2os5wizlm\r\n# hosts
e
URL=\r\nN8N_HOST=https://n8n2.ljit.com.br\r\nN8N_EDITOR_BASE_URL=https://n8n2.ljit.com.br\r\n
N8N_PROTOCOL=https\r\nNODE_ENV=production\r\n#
webhooks=\r\nWEBHOOK_URL=https://n8n2webhook.ljit.com.br\r\n# modo de execucao para
fila=\r\nEXECUTIONS_MODE=queue\r\n#
redis=\r\nQUEUE_BULL_REDIS_HOST=main_n8n_redis\r\nQUEUE_BULL_REDIS_PASSWORD=ecnc01
pq5761u9xra5ss\r\nQUEUE_BULL_REDIS_PORT=6379\r\nQUEUE_BULL_REDIS_DB=2\r\n#
bibliotecas
utilizadas=\r\nNODE_FUNCTION_ALLOW_EXTERNAL=*
\r\nEXECUTIONS_DATA_PRUNE='true'\r\nEXE
CUTIONS_DATA_MAX_AGE=336\r\n#timezone=\r\nGENERIC_TIMEZONE=America/Sao_Paulo\r\nN8N
_ENFORCE_SETTINGS_FILE_PERMISSIONS=true\r\nN8N_RUNNERS_ENABLED=true\r\nN8N_RUNNERS
_MODE=internal\r\nOFFLOAD_MANUAL_EXECUTIONS_TO_WORKERS=true\r\nN8N_NODE_PATH=/ho
me/node/.n8n/nodes",
      "deploy": {
        "replicas": 1,
        "command": "n8n start",
        "zeroDowntime": true
      },
      "domains": [
        {
```

```

    "host": "n8n2.ljit.com.br",
    "https": true,
    "port": 5678,
    "path": "/",
    "middlewares": [],
    "certificateResolver": "",
    "wildcard": false,
    "internalProtocol": "http"
  }
]
},
{
  "type": "app",
  "data": {
    "projectName": "main",
    "serviceName": "n8n_mcp_wh",
    "source": {
      "type": "image",
      "image": "n8nio/n8n:latest"
    },
    "env":
"DB_TYPE=postgresdb\r\nDB_POSTGRESDB_PORT=5432\r\nDB_POSTGRESDB_HOST=main_n8n_pos
gres\r\nDB_POSTGRESDB_DATABASE=n8n\r\nDB_POSTGRESDB_USER=postgres\r\nDB_POSTGRES
DB_PASSWORD=e8a8bhc40zj2os5wizlm\r\n# criar chave
https://acte.ltd/utils/randomkeygen=\r\nN8N_ENCRYPTION_KEY=e8a8bhc40zj2os5wizlm\r\n# hosts
e
URL=\r\nN8N_HOST=https://n8n2.ljit.com.br\r\nN8N_EDITOR_BASE_URL=https://n8n2.ljit.com.br\r\n
N8N_PROTOCOL=https\r\nNODE_ENV=production\r\n#
webhooks=\r\nWEBHOOK_URL=https://n8n2webhook.ljit.com.br\r\n# modo de execucao para
fila=\r\nEXECUTIONS_MODE=queue\r\n#
redis=\r\nQUEUE_BULL_REDIS_HOST=main_n8n_redis\r\nQUEUE_BULL_REDIS_PASSWORD=ecnc01
pq5761u9xra5ss\r\nQUEUE_BULL_REDIS_PORT=6379\r\nQUEUE_BULL_REDIS_DB=2\r\n#
bibliotecas
utilizadas=\r\nNODE_FUNCTION_ALLOW_EXTERNAL=*\r\nEXECUTIONS_DATA_PRUNE='true'\r\nEXE
CUTIONS_DATA_MAX_AGE=336\r\n#timezone=\r\nGENERIC_TIMEZONE=America/Sao_Paulo\r\nN8N
_ENFORCE_SETTINGS_FILE_PERMISSIONS=true\r\nN8N_RUNNERS_ENABLED=true\r\nN8N_RUNNERS
_MODE=internal\r\nOFFLOAD_MANUAL_EXECUTIONS_TO_WORKERS=true\r\nN8N_NODE_PATH=/ho
me/node/.n8n/nodes",
    "deploy": {
      "replicas": 1,
      "command": "n8n webhook",
      "zeroDowntime": true
    },
    "domains": [
      {
        "host": "n8n-mcp-wh.eu.com.br",

```

```

    "https": true,
    "port": 5678,
    "path": "/mcp",
    "middlewares": [],
    "certificateResolver": "",
    "wildcard": false,
    "internalProtocol": "http"
  }
]
}
},
{
  "type": "postgres",
  "data": {
    "projectName": "main",
    "serviceName": "n8n_postgres",
    "image": "postgres:17",
    "password": "e8a8bhc40zj2os5wizlm"
  }
},
{
  "type": "redis",
  "data": {
    "projectName": "main",
    "serviceName": "n8n_redis",
    "image": "redis:7",
    "password": "ecnc01pq5761u9xra5ss"
  }
},
{
  "type": "app",
  "data": {
    "projectName": "main",
    "serviceName": "n8n_webhook",
    "source": {
      "type": "image",
      "image": "n8nio/n8n:latest"
    }
  },
  "env":

```

```

"DB_TYPE=postgresdb\r\nDB_POSTGRESDB_PORT=5432\r\nDB_POSTGRESDB_HOST=main_n8n_pos
tgres\r\nDB_POSTGRESDB_DATABASE=n8n\r\nDB_POSTGRESDB_USER=postgres\r\nDB_POSTGRES
DB_PASSWORD=e8a8bhc40zj2os5wizlm\r\n# criar chave
https://acte.ltd/utils/randomkeygen=\r\nN8N_ENCRYPTION_KEY=e8a8bhc40zj2os5wizlm\r\n# hosts
e
URL=\r\nN8N_HOST=https://n8n2.ljit.com.br\r\nN8N_EDITOR_BASE_URL=https://n8n2.ljit.com.br\r\n
N8N_PROTOCOL=https\r\nNODE_ENV=production\r\n#
webhooks=\r\nWEBHOOK_URL=https://n8n2webhook.ljit.com.br\r\n# modo de execucao para

```

```
fila=\r\nEXECUTIONS_MODE=queue\r\n#
redis=\r\nQUEUE_BULL_REDIS_HOST=main_n8n_redis\r\nQUEUE_BULL_REDIS_PASSWORD=ecnc01
pq5761u9xra5ss\r\nQUEUE_BULL_REDIS_PORT=6379\r\nQUEUE_BULL_REDIS_DB=2\r\n#
bibliotecas
utilizadas=\r\nNODE_FUNCTION_ALLOW_EXTERNAL=* \r\nEXECUTIONS_DATA_PRUNE='true'\r\nEXE
CUTIONS_DATA_MAX_AGE=336\r\n#timezone=\r\nGENERIC_TIMEZONE=America/Sao_Paulo\r\nN8N
_ENFORCE_SETTINGS_FILE_PERMISSIONS=true\r\nN8N_RUNNERS_ENABLED=true\r\nN8N_RUNNERS
_MODE=internal\r\nOFFLOAD_MANUAL_EXECUTIONS_TO_WORKERS=true\r\nN8N_NODE_PATH=/ho
me/node/.n8n/nodes",
  "deploy": {
    "replicas": 2,
    "command": "n8n webhook",
    "zeroDowntime": true
  },
  "domains": [
    {
      "host": "n8n2webhook.ljit.com.br",
      "https": true,
      "port": 5678,
      "path": "/",
      "middlewares": [],
      "certificateResolver": "",
      "wildcard": false,
      "internalProtocol": "http"
    }
  ]
},
{
  "type": "app",
  "data": {
    "projectName": "main",
    "serviceName": "n8n_worker",
    "source": {
      "type": "image",
      "image": "n8nio/n8n:latest"
    },
    "env":
      "DB_TYPE=postgresdb\r\nDB_POSTGRESDB_PORT=5432\r\nDB_POSTGRESDB_HOST=main_n8n_pos
      tgres\r\nDB_POSTGRESDB_DATABASE=n8n\r\nDB_POSTGRESDB_USER=postgres\r\nDB_POSTGRES
      DB_PASSWORD=e8a8bhc40zj2os5wizlm\r\n# criar chave
      https://acte.ltd/utils/randomkeygen=\r\nN8N_ENCRYPTION_KEY=e8a8bhc40zj2os5wizlm\r\n# hosts
      e
      URL=\r\nN8N_HOST=https://n8n2.ljit.com.br\r\nN8N_EDITOR_BASE_URL=https://n8n2.ljit.com.br\r\n
      N8N_PROTOCOL=https\r\nNODE_ENV=production\r\n#
      webhooks=\r\nWEBHOOK_URL=https://n8n2webhook.ljit.com.br\r\n# modo de execucao para
      fila=\r\nEXECUTIONS_MODE=queue\r\n#
```

```
redis=\r\nQUEUE_BULL_REDIS_HOST=main_n8n_redis\r\nQUEUE_BULL_REDIS_PASSWORD=ecnc01
pq5761u9xra5ss\r\nQUEUE_BULL_REDIS_PORT=6379\r\nQUEUE_BULL_REDIS_DB=2\r\n#
bibliotecas
utilizadas=\r\nNODE_FUNCTION_ALLOW_EXTERNAL=*r\nEXECUTIONS_DATA_PRUNE='true'\r\nEXE
CUTIONS_DATA_MAX_AGE=336\r\n#timezone=\r\nGENERIC_TIMEZONE=America/Sao_Paulo\r\nN8N
_ENFORCE_SETTINGS_FILE_PERMISSIONS=true\r\nN8N_RUNNERS_ENABLED=true\r\nN8N_RUNNERS
_MODE=internal\r\nOFFLOAD_MANUAL_EXECUTIONS_TO_WORKERS=true\r\nN8N_NODE_PATH=/ho
me/node/.n8n/nodes",
  "deploy": {
    "replicas": 1,
    "command": "n8n worker --concurrency=10",
    "zeroDowntime": true
  },
  "domains": [
    {
      "host": "n8n-worker.eu.com.br",
      "https": true,
      "port": 80,
      "path": "/",
      "middlewares": [],
      "certificateResolver": "",
      "wildcard": false,
      "internalProtocol": "http"
    }
  ]
}
```

Revision #1

Created 19 May 2026 23:12:24 by Admin

Updated 19 May 2026 23:13:51 by Admin